

المحولات الكهربائية



400 Kv

CUSTOMER		Onil General Trade Import & Export General Manager Adel M.Azaldeen Telephon +963 31 2230039		Mobil +963 92654420 Mobil +963 96720004 Fax +963 31 2230038	
STANDARDS IN FORCE			IEC 60076		
TYPE OF TRANSFORMER			OUTDOOR/OIL IMMERSED HERMETICALLY		
TRANSFORMER OIL			Shell Diata AX (Non PCB)		
TANK PAINTING			RAL7033(Non Galvanized)		
NUMBER OF BHASE			3		
FREQUENCY			50HZ		
RATED POWER			400Kva		
RATED VOLTAGES			11/0.416KV		
NO.LOAD LOSSES			930W +15%		
LOAD LOSSES			4600W+15%		
VOLTAGE REGULATION RANGE			+- 2*2.5% (off load tap changer)		
IMPEDANCE VOLTAGE 75C			4%		
VECTOR GROUP			Dyn 11		
TYP OF COOLING			ONAN		
WINDINGS TEMPERATURE RISE			65C		
MAXIMUM OIL TEMPERATURE RISE			60C		
H.V.and.L.V.BUSHING			Porcelain open type-porcelain open type		
OPERATION MODE			CONTINUOUSLY		
WEIGHT	Total weight	1670kg			
	Oil Weight	390kg			
	Weight of active	970 kg			
DAMEMENSION	Length	1250mm			
	Width	1018mm			
	Height	1720mm			
ACCESSORIES SUPPLYIDE WITH TRANSFORMER			Marking Plats		
			Off-load Tap Changer		
			Thermometer Pocket		
			lifting Lugs		
			T10 Pressure Relief Valve		
			Drain Valve		
			Earthing Terminal on Tank		
			Oil level indicator slod		

المحطات الكهربائية

